

Lite Master | 2'

Lite Master T8 is good for efficient lighting where functional requirements of basic lighting is taken care off.

- Retrofit design for T8
- Better light output
- Energy saving upto 50%
- Inbuilt LED driver
- Extruded aluminum profile with polycarbonate casing
- Easy to install
- Weight : 0.4 Kg



Code - 24 09 02.144

| | |
|-------------------|-----------------------------|
| Type | • SMD |
| Power Consumption | • 10W ± 10% |
| IP Rating | • 20 |
| Operating Voltage | • 90-270 V AC or 90-140V DC |
| Color Temperature | • CW/WW |
| Luminous Efficacy | • > 100 lm/W |
| CRI | • > 80 |
| Power Factor | • > 0.95 |
| THD | • < 15% |

Lite Master | 4'

Lite Master T8 is good for efficient lighting where functional requirements of basic lighting is taken care off.

- Retrofit design for T8, easy to install
- Better light output
- Inbuilt LED driver
- Extruded aluminum profile with polycarbonate casing
- IP Rating: 20
- Operating Voltage: 90-270V AC or 90-140VDC
- LM-79 certified.
- Weight : 0.7 Kg



Code - 25 09 02.288

| | |
|-------------------|----------------|
| Code | • 25 09 02.288 |
| Power Consumption | • 20W±10% |
| Luminous Efficacy | • > 100 lm/W |
| CRI | • > 80 |
| Power Factor | • > 0.95 |
| THD | • < 15% |

